







MATERIAL SPECIFICATIONS WIRE STAPLE

Materials:

Hard Drawn Steel Wire

Dimensions:

11 gauge, 6.0 in x 1.0 in x 6.0 in (15.2 cm x 2.5 cm x 15.2 cm) 8 gauge, 8.0 in x 2.0 in x 8.0 in (20.3 cm x 5.1 cm x 20.3 cm)

Description:

American Excelsior Company provides steel wire staples that may be utilized to anchor erosion control blankets (ECBs), turf reinforcement mats (TRMs), sod, landscape fabric, and filter fabric. Product-specific Staple Pattern Guides shall be followed when anchoring ECBs and TRMs.

Six inch steel wire staples are available in boxes of 100 or 1,000 staples per box. Eight inch steel wire staples are available in boxes of 500 staples per box.

Physical Properties:

Material: Hard Drawn Steel Wire Weight: $6 \text{ in: } 0.6 \text{ oz } (17 \text{ g}) \pm 3\%$

8 in: 1.6 oz $(45.4 g) \pm 1\%$

Leg Length: $6 \text{ in } (15.2 \text{ cm}) \pm 0.25 \text{ in}$

8 in $(20.3 \text{ cm}) \pm 0.25 \text{ in}$

Number of Legs: Two per Staple

Diameter: 11 gauge, $0.115 \text{ in } \pm 0.003 \text{ in } (0.292 \text{ cm } \pm 0.008 \text{ cm})$

8 gauge, 0.157 in ± 0.003 in $(0.399 \text{ cm} \pm 0.008 \text{ cm})$

Head Configuration: U-Shaped

Head Width: 1.0 in (2.5 cm) for 6 in

2.0 in (5.1 cm) for 8 in









MANUFACTURER'S CERTIFICATION STEEL WIRE STAPLES - Anchoring Devices

Provider:

American Excelsior Company 831 Pioneer Avenue Rice Lake, WI 54868 1-866-9FIBERS (1-866-934-2377)

Project Information (if applicable):

Name:
Location:

Number:

Statement

We hereby certify that the above referenced material is manufactured to meet or exceed the following specification:

Material: Hard Drawn Steel Wire Weight: 6 in: 0.6 oz $(17 g) \pm 3\%$

8 in: 1.6 oz (45.4 g) \pm 1%

Leg Length: $6 \text{ in } (15.2 \text{ cm}) \pm 0.25 \text{ in}$

8 in $(20.3 \text{ cm}) \pm 0.25 \text{ in}$

Number of Legs: Two per Staple

Diameter: $11 \text{ gauge}, 0.115 \text{ in } \pm 0.003 \text{ in } (0.292 \text{ cm } \pm 0.008 \text{ cm})$

8 gauge, 0.157 in ± 0.003 in $(0.399 \text{ cm} \pm 0.008 \text{ cm})$

Head Configuration: U-Shaped

Head Width: 1.0 in (2.5 cm) for 6 in

2.0 in (5.1 cm) for 8 in

Tony Johnson – General Manager, Rice Lake

Effective Date

Note: This Certification expires, without notice, if document is updated by American Excelsior Company (AEC). Current Material Specifications and Manufacture's Certifications (MSMC) for AEC products shall be accessed from www.Curlex.com at all times.